



43" Stander Digital Signage (Cloud)

Options

Color: Black | White | Tailored Accessories: Lockable Wheels













178°view angle

Display 43" Active Display Area (nm) 531 (H) 943 (V) Max Resolution 1920 x 1080 Screen Ratio 16 : 9 Brightness 350 cd/m² Contrast 5000 : 1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RX 3288 Cortex-A17 Quad Core 1.8 GHz GPU		wifi screen RSS schedule a.i. angle
Panel Size (Diagonal) 43" Active Display Area (mm) 531 (H) 943 (V) Max Resolution 1920 x 1080 Screen Ratio 16:9 Brightness 350 cd/m² Contrast 5000:1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - 1764 RAM 4GB DDR3 Storage 166B Input Terminals USB 2.0 x 2 LAN Supported Format Video Wideo mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000) x 15,000) Audio mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images	Model Number	NW-SDK43
Active Display Area (mm) Max Resolution 1920 x 1080 Screen Ratio 16:9 Brightness 350 cd/m² Contrast 5000:1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 124 bit Viewing Angle Light Source LED Operational Life Time System Operating System CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU RK 3288 Cortex-A17 Quad Core 1.9 GHz GPU RK 328 Cortex-A17 Quad Core 1.9 GHz GPU RK 328 Cortex-A17 Qua	Display	
Max Resolution 1920 x 1080 Screen Ratio 16 : 9 Brightness 350 cd/m² Contrast 5000 : 1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - 1764 RAM 4 GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Video Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption < 575W ~ ≤ 175W	Panel Size (Diagonal)	43"
Screen Ratio 16:9 Brightness 350 cd/m² Contrast 5000:1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Operating System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Video Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption < 75W ~ ≤ 175W	Active Display Area (mm)	531 (H) 943 (V)
Brightness 350 cd/m²	Max Resolution	1920 x 1080
Contrast 5000:1 Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Wideo Wideo mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption < 75W ~ ≤ 175W	Screen Ratio	16:9
Brightness Uniformity > 70% Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android OPERATING System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Wideo Wideo mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption < 75W ~ ≤ 175W	Brightness	350 cd/m ²
Response Time 6 ms Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Operating System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption Power Source 100 V ~ 240 V, 50 ~ 60 Hz Operational Power Consimption < 5W	Contrast	5000:1
Max Frame Rate 30 frm/s Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Operating System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption ≤ 75W ~ ≤ 175W Standby Power Consumption ≤ 75W ~ ≤ 175W Standby Power Consimption < 5W	Brightness Uniformity	> 70%
Display Colors 24 bit Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Wideo Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv m Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption ≤ 75W ~ ≤ 175W Standby Power Consimption < 5W	Response Time	6 ms
Viewing Angle 178 / 178 Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format wideo Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption mp2 mp3 wma wav Power Source 100 V ~ 240 V, 50 ~ 60 Hz Operational Power Consimption < 5W	Max Frame Rate	30 frm/s
Light Source LED Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Wideo Wideo mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption ToV ~ 240 V, 50 ~ 60 Hz Operational Power Consimption < 75W ~ ≤ 175W Standby Power Consimption < 5W Physical Specification 46 kg ± 1.5 kg Dimensions (W x D x H) (mm) 583 x 70 x 1755	Display Colors	24 bit
Operational Life Time > 50,000 hours System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format which is to be a provided for the property of the pr	Viewing Angle	178 / 178
System Android CPU RK 3288 Cortex-A17 Quad Core 1.8 GHz GPU ARM Mali - T764 RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Wideo Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption 275W ~ ≤ 175W Standby Power Consimption < 5W Physical Specification 46 kg ± 1.5 kg Weight 46 kg ± 1.5 kg Dimensions (W x D x H) (mm) 583 x 70 x 1755	Light Source	LED
Operating SystemAndroidCPURK 3288 Cortex-A17 Quad Core 1.8 GHzGPUARM Mali - T764RAM4GB DDR3Storage16GBInput TerminalsUSB $2.0 \times 2 \mid \text{LAN}$ Supported FormatVideompeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rmImagesjpeg png (Max Resolution : 15,000 x 15,000)Audiomp2 mp3 wma wavPower ConsumptionPower Source $100 \text{ V} \sim 240 \text{ V}$, $50 \sim 60 \text{ Hz}$ Operational Power Consimption $\leq 75\text{W} \sim 175\text{W}$ Standby Power Consimption $< 5\text{W}$ Physical SpecificationWeight $46 \text{ kg} \pm 1.5 \text{ kg}$ Dimensions (WxDxH) (mm) $583 \times 70 \times 1755$	Operational Life Time	> 50,000 hours
$ \begin{array}{c} CPU & RK3288Cortex-A17QuadCore1.8GHz \\ GPU & ARMMali \cdot T764 \\ RAM & 4GBDDR3 \\ Storage & 16GB \\ InputTerminals & USB2.0x2\mid LAN \\ SupportedFormat \\ Video & mpeg2 $	System	
$\begin{array}{c ccccc} GPU & & & & & ARM\ Mali-T764 \\ RAM & & & & & & & & & & \\ Storage & & & & & & & & \\ Input\ Terminals & & & & & & & \\ Supported\ Format & & & & & & & \\ Video & & & & & & & & \\ Images & & & & & & & \\ Images & & & & & & & \\ Images & & & & & & & \\ Images & & & & & & & \\ Images & & & & & & & \\ Images & & & & & & & \\ Images & & & & \\ Images & & & & & \\ Images & & & \\ Images & & & \\ Images & & & & \\ Images & & & \\ Images & & & & \\ Images & & & $		
RAM 4GB DDR3 Storage 16GB Input Terminals USB 2.0 x 2 LAN Supported Format Video mpeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rm Images jpeg png (Max Resolution : 15,000 x 15,000) Audio mp2 mp3 wma wav Power Consumption Power Source 100 V ~ 240 V, 50 ~ 60 Hz Operational Power Consumption ≤ 75W ~ ≤ 175W Standby Power Consimption < 5W Physical Specification Weight 46 kg ± 1.5 kg Dimensions (W x D x H) (mm) 583 x 70 x 1755		· · · · · · · · · · · · · · · · · · ·
Storage16GBInput TerminalsUSB 2.0 x 2 LANSupported FormatTrack of the point of		
Input Terminals $USB 2.0 \times 2 \mid LAN$ Supported Format Video $mpeg2 \mid avi \mid mp4 \mid div \mid ts \mid tp \mid trp \mid mkv \mid mov \mid dat \mid asf \mid wmv \mid rm$ Images $jpeg \mid png (Max Resolution : 15,000 \times 15,000)$ Audio $mp2 \mid mp3 \mid wma \mid wav$ Power Consumption Power Source $100 \lor \sim 240 \lor V, 50 \sim 60 \thickspace Hz$ Operational Power Consumption $\leq 75W \sim \leq 175W$ Standby Power Consimption $< 5W$ Physical Specification Weight $46 \space kg \pm 1.5 \space kg$ Dimensions ($W \times D \times H$) (mm) $583 \times 70 \times 1755$	RAM	
Supported FormatVideo $mpeg2 \mid avi \mid mp4 \mid div \mid ts \mid tp \mid trp \mid mkv \mid mov \mid dat \mid asf \mid wmv \mid rm$ Images $jpeg \mid png (Max Resolution : 15,000 \times 15,000)$ Audio $mp2 \mid mp3 \mid wma \mid wav$ Power Consumption $mp2 \mid mp3 \mid wma \mid wav$ Power Source $100 \lor \sim 240 \lor, 50 \sim 60 \thickspace Hz$ Operational Power Consumption $\leq 75W \sim \leq 175W$ Standby Power Consimption $< 5W$ Physical Specification $46 \lor kg \pm 1.5 \lor kg$ Weight $46 \lor kg \pm 1.5 \lor kg$ Dimensions ($W \times D \times H$) (mm) $583 \times 70 \times 1755$	Storage	1.7
Videompeg2 avi mp4 div ts tp trp mkv mov dat asf wmv rmImagesjpeg png (Max Resolution : 15,000 x 15,000)Audiomp2 mp3 wma wavPower Consumption $000000000000000000000000000000000000$		USB 2.0 x 2 LAN
Imagesjpeg png (Max Resolution : 15,000 x 15,000)Audiomp2 mp3 wma wavPower Consumption $100 \text{ V} \sim 240 \text{ V}, 50 \sim 60 \text{ Hz}$ Power Source $100 \text{ V} \sim 240 \text{ V}, 50 \sim 60 \text{ Hz}$ Operational Power Consumption $\leq 75W \sim \leq 175W$ Standby Power Consimption $< 5W$ Physical Specification $46 \text{ kg} \pm 1.5 \text{ kg}$ Weight $46 \text{ kg} \pm 1.5 \text{ kg}$ Dimensions (W x D x H) (mm) $583 \times 70 \times 1755$	the state of the s	
Audio $mp2 \mid mp3 \mid wma \mid wav$ Power Consumption $100 \lor \sim 240 \lor, 50 \sim 60 Hz$ Power Source $100 \lor \sim 240 \lor, 50 \sim 60 Hz$ Operational Power Consumption $\leq 75W \sim \leq 175W$ Standby Power Consimption $< 5W$ Physical Specification $46 \lg \pm 1.5 \lg$ Weight $46 \lg \pm 1.5 \lg$ Dimensions ($ W x D x H) $ ($ mm $) $583 \times 70 \times 1755$	Video	
Power ConsumptionPower Source $100 \text{ V} \sim 240 \text{ V}$, $50 \sim 60 \text{ Hz}$ Operational Power Consumption $\leq 75W \sim \leq 175W$ Standby Power Consimption $< 5W$ Physical Specification $46 \text{ kg} \pm 1.5 \text{ kg}$ Weight $46 \text{ kg} \pm 1.5 \text{ kg}$ Dimensions (W x D x H) (mm) $583 \times 70 \times 1755$	Images	
Power Source $100 \text{ V} \sim 240 \text{ V}$, $50 \sim 60 \text{ Hz}$ Operational Power Consumption $\leq 75 \text{W} \sim \leq 175 \text{W}$ Standby Power Consimption $< 5 \text{W}$ Physical SpecificationWeight $46 \text{ kg} \pm 1.5 \text{ kg}$ Dimensions (W x D x H) (mm) $583 \times 70 \times 1755$	Audio	mp2 mp3 wma wav
Operational Power Consumption $\leq 75 \text{W} \sim \leq 175 \text{W}$ Standby Power Consimption $< 5 \text{W}$ Physical Specification46 kg \pm 1.5 kgWeight46 kg \pm 1.5 kgDimensions (W x D x H) (mm)583 x 70 x 1755	Power Consumption	
Standby Power Consimption < 5W	Power Source	
Physical Specification Weight 46 kg ± 1.5 kg Dimensions (W x D x H) (mm) 583 x 70 x 1755	Operational Power Consumption	≤ 75W ~ ≤ 175W
Weight 46 kg ± 1.5 kg Dimensions (W x D x H) (mm) 583 x 70 x 1755	Standby Power Consimption	< 5W
Dimensions (W x D x H) (mm) 583 x 70 x 1755	Physical Specification	
	Weight	46 kg ± 1.5 kg
Base Dimensions (W x D x H) (mm) 595 x 420 x 1800	Dimensions (W x D x H) (mm)	583 x 70 x 1755
	Base Dimensions (W x D x H) (mm)	595 x 420 x 1800

^{*}Product specifications are subject to change without notice

- Embedded with powerful cloud-based signage system, supporting Android, IOS, and windows content player
- Central management of the entire digital signage network including user control, live server status, network health reports, application management, user privileges control
- Support landscape and portrait content broadcast
- Support screen-split
- Watchdog function has the power to restart the SignagePlayer and put it back into normal operation
- Broadcast toolkits to support scheduling, campaign group, weather broadcast
- Real-time trace and track to monitor the status of all player stations
- Support Really Simple Syndication (RSS) to receive and play dynamic news feeds
- Support website plug-in to allows users to drag in a website page by full screen or split-screen
- Support QR Code generation